

UKM-series



True On-line Double Conversion UPS

6 kVA - 10 kVA

- Full digital microprocessor control
- Wide input voltage range
- UPS startup without battery
- Cold start function
- ECO mode operation for energy saving
- Emergency Power Off (EPO) function
- Advanced battery management
- Automatic battery charging in UPS off mode
- Lightning and surge protection
- Short circuit and overload protection
- EMI/RFI noise filter
- USB and RS-232 communication port
- SNMP/HTTP capability (option)
- Extend backup time (option)
- UPS monitoring and management software (option)
- Suit for computer network, servers and other IT equipments
- Product from ISO 9001 and ISO 14001 certified factory



MODEL		UKM-6000	UKM-10000
CAPACITY	For computer load	6 kVA / 5.4 kW	10 kVA / 9kW
INPUT	Phase	3 phase 4 wires and ground or single phase & ground	
	Voltage	380 / 400 / 415 Vac or 220 / 230 / 240 Vac	
	Voltage range	208 - 478 Vac or 120 - 276 Vac	
	Frequency	40 Hz - 70 Hz	
	Power factor	more than 0.99 at full load	
OUTPUT	Voltage range	220 Vac \pm 1%	
	Phase	single phase	
	Frequency	50 Hz \pm 0.1 Hz	
	Wave form	pure sine wave	
	Total Harmonic distortion	\leq 2% of THD at linear load, \leq 5% of THD at non-linear load	
	Overload capability	110% ~ 125% for 10 min., 125% ~ 150% for 1 min., \geq 150% for 200 sec.	
	Crest factor ratio	3:1	
	Short circuit protection	turn off inverter, no transfer to bypass, audible alarm (AC mode) turn off inverter, audible alarm (Battery mode)	
	Efficiency (AC mode)	90%	
	Protection	overload, over / under voltage, short circuit proof and battery low voltage shutdown	
	TRANSFER TIME	Between AC mode and Battery mode zero time (True on-line UPS)	
PROTECTION	EMI/RFI attenuation	IEC 62040-2	
	Surge protection	IEC 61000-4-5	
BATTERY EXTENSION	Type	sealed lead acid (maintenance free) rechargeable	
	Capacity	12 V 9 Ah x 20	
	Backup time	15 minutes (depending on computer load)	
	Extended backup time	option	
	Continuous recharging time	90% capacity after 5 hours charging	
INDICATOR	Status LED & LCD	Line mode, Backup mode, Eco mode, Bypass mode, Low battery, Bad battery, Overload & UPS fault	
	Read on the LCD	Input voltage / frequency, Battery voltage, Output voltage / frequency, Load level (%), Inner temperature, Remaining backup time	
AUDIBLE ALARM	Buzzer	Battery mode, low battery, overload, fault	
COMMUNICATION INTERFACE	RS-232 port, RS-485 port	yes	
	USB port	yes	
	SNMP/HTTP capability	option	
SOFTWARE (1)	UPS monitoring and management software	option	
ACOUSTIC NOISE	At 1 metre	< 55 dBA	
ENVIRONMENT	Temperature	0 - 40°C	
	Relative humidity	0 - 95% (non-condensing)	
DIMENSIONS	UPS	44 x 13 x 58 (3U)	
W x H x D (cm)	Battery extension unit	Tower 45 x 44 x 50cm (Rack mount 44 x 13 x 68 cm(3U) is optional)	
WEIGHT	UPS	25 kg	
Approx. in kg.	Battery extension unit	63 kg	

Continuous product development is our commitment. In that manner, the above specifications may be changed without prior notice.



บริษัท แสง (ประเทศไทย) จำกัด

568/4 ซอยลาดพร้าว 112 (เอี่ยมสมบูรณ์) ถนนลาดพร้าว แขวงพลับพลา เขตวังทองหลาง กรุงเทพมหานคร 10310

โทรศัพท์ : 02 026 3364 ต่อ 114

www.saeng.co.th